

## **EUROPEAN INSPECTION AND CERTIFICATION COMPANY S.A.**

EU TYPE-EXAMINATION CERTIFICATE FOR SAFETY COMPONENTS ACCORDING TO EUROPEAN LIFT DIRECTIVE 2014/33/EU ANNEX IV (MODULE B)

ACCORDING TO LORGI EAR EIT I DIRECTIVE 2014/35/EG ARREA IV (MODULE B)	
Certificate Number:	SCMB.0061
Certificate Expiry Date:	16.01.2027
Applicant/Certificate Holder	Ningbo Xinda Elevator Accessories Co., Ltd./
(Name & Address):	Dongwu Town, Ningbo City, Zhejiang Province,
*	China
Manufacturer	Same as applicant
(Name & Address):	
Date of Submission:	10.11.2016
Test Laboratory	Shenzhen Institute of Special Equipment Inspection
(Name & Address):	and test / No.1032, Honggang Road, Luohu
	District, Shenzhen, Guangdong, China
Date and Number of test report:	01.07.2016 /2016AF1203
Approved Type of ascending car overspeed protection	Braking Device as part of the Lift Ascending
means:	Overspeed protection Means
Application of ascending car overspeed protection	Acting on the shaft of the traction sheave, as part
means:	of the protection device against overspeed of the
	car moving in upwards direction
Model of ascending car overspeed protection means:	DB
Drawing Number (attached to this certificate):	Z11520000
Standard(s):	2014/33/EU, EN81-50:2014
Reference Standard(s):	EN 81-20:2014

EUROCERT SA, aforementioned notified body with identification number 1128, ascertains and certifies that above safety component satisfy the safety requirements of the European Directive 2014/33/EU.

The manufacturer is authorized to provide the safety component described above with the CE Mark as displayed below:

(€1128

Preconditions:

It is required that the above safety equipment must always come with a declaration of conformity and the relevant instructions of use.

INSPECTOR

hens 17/01/2017

,

FOR EUROCERT SA

GEORGE NIKO LOPOULOS

Technical Director

Please check the validity of the certificate from our website using the password kEWap98e



Inspections Cert No.: 53-3 .13.6/E20/16-01-2014 89, CHLOIS STR. & LIKOVRISEOS, 144 52 METAMORFOSI, ATHENS, GREECE Tel.: ++30 210 62.52.495, 30 210 62.53.927 - Fax: ++30 210 62.03.018 Internet site: www.eurocert.gr - e-mail: eurocert@otenet.gr



Page 1 of 2



## **EUROPEAN INSPECTION AND CERTIFICATION COMPANY S.A.**

## ANNEX A TO CERTIFICATE SCMB.0061

## **TECHNICAL DESCRIPTION**

Product Name/Product Type / Model

BRAKING ELEMENT AS PART OF THE ASCENDING CAR

OVERSPEED PROTECTION MEANS / DZS

Type of Application

Braking Device acting on the shaft of the traction sheave

Permissible system total mass

(empty car mass + counterweight e.t.c.)

: 1200-7750(Kg)

Permissible car mass

: 520-3250(Kg)

Permissible rated load with suspension

ratio of 2:1

320-2500(Kg)

Range of balance coefficient

0.40 - 0.50

Tripping speed range of overspeed

100

0.35-5.06(m/sec)

governor

: 0.3-4.0 (m/sec)

Every Safety Component must be labeled

with the following information

Rated speed range of elevator

Manufacturer's Name Safety Components Type

Conditions :

- 1) Since the brake device represents only a part of the protection device against overspeed for the car moving in upwards direction an overspeed governor as per EN 81-20, paragraph 5.6.2.2.1 must be used to monitor the upward speed as well as the downwards speed and the brake device must be triggered (engaged) via the overspeed governor's electric safety device.
- 2) The mechanical movement of each brake circuit is to be monitored separately and directly. If a brake circuit fails to engage (close) while the lift machine is at standstill, next movement of the lift must be prevented.

3) In cases where the lift machine moves despite the brake being engaged (closed), the lift machine must at the latest be stopped and the next movement of the lift must be prevented.



